

Tear Tape Product Test Report				
Manufacturer: Asia Pacific Industry Group Co., Limited				
Commodity	Self AdhesiveTear Tape		quantity	
Standard	Q/SZ 104 017-2018			
Standards measured	Unit	test indicators	real value data	individual judgment
Width	mm	2.0±0.1	2.0	Qualified
Tensile strength	N/2.5m m	≥13	13.6	Qualified
Elongation at break	%	≤170	152.3	Qualified
180 ° peel strength	N/cm	≥0.12	0.7	Qualified
Holding adhesive	min	≥30	60	Qualified
Winding way	-	A/B	-	Qualified
Adhesive layer	--	Rubber face, the layer uniform, transparent and clear, no dust and impurities.	satisfy	Qualified

Exterior	surface	--	Surface smooth, uniform color, flush on both sides, no creases, excess glue, stain, when unwinding non-adhesive surface without adhesive residue.	satisfy	Qualified
	Core	--	Solid, no distortion, no dents, nicks, loose and into the end face. It should be wound neatly, no scratches, no edges, no dislocation.	satisfy	Qualified
	surface	--	Clear and complete printed pattern, position, size ratio with the design requirements, no color.	satisfy	Qualified
	Pattern printing	--	Handwriting, lines, symbols, clear and full, centered.	satisfy	Qualified
final decision	Qualified				